

OC-F08 Fixed gas detector



Description:

OC-F08 series fixed gas detector used the original imported sensor and the ultra low power 32 bit microprocessor, so with the advantages of high precision, good repeatability, stable signal, respond quickly, etc. Possible connected with many controller system, such as PLC, DCS, computer and other, with the function of remote monitor and alarm, data logger and analysis.

Common applications is gas safety inspection and alarm for industrial scene, such as petroleum refinery, chemical plants, LPG stations, boiler rooms, gas stations, paint spray booths, metallurgy, mining, fire, environmental protection, etc.

Features:

4-20mA standard analog signal and RS485 digital signal output, 200~1000HZ signal output, relay output, data restore, data logger(optional);

LED screen displaying the gas concentration, gas type, unit, instrument status etc.

Independent air chamber, the sensor is not required to replace the sensor calibration, automatic identification of key parameters of the sensor;

Protection function to prevent high gas concentration attack;

Display the gas concentration in ppm, %LEL, %vol and mg/m³ is selectable;

Infrared remote controller operation;

With the 16bit ADC acquisition chip, designed with four-layer circuit board, so with high anti-interference ability;

With the Ex-proof certificate, the Ex-proof grade is Exd II CT6.

Technical Parameter:

Detection Gas	Oxygen, Combustible gas, toxic gas, etc
Detecting Range	According to the detected gas
Resolution	According to the detected gas
Sampling	Diffusion or pump-suction, circulation selectable
Precision	≤±3%F.S
Repeatability	≤±1%
Zero drift	≤±1%(F.S/year)
Sensor Type	Catalytic combustion , Electrochemical, PID, Infrared sensor
Sensor Life	2~3 years(Catalytic combustion, Electrochemical, Semiconductor) 3~5 years(PID, Infrared)
Response Time (T90)	≤20s
Alarming mode	Audible-visual alarm (Optional)
Operating Environment	Temperature: -30℃~60℃ (Customized for special demands) Humidity: ≤95%RH (non-condensing); if >90%RH, can add the filter Pressure: 86kPa~106kPa
Working Voltage	24V DC(16~30VDC)
Output Signals	(Standard)Three-wire system 4~20mA standard signals output, available for PLC, DCS, etc; (Optional) Four-wire system RS485 digital signal output; (Optional) Frequency signal 200~1000Hz output; Two-level relay output:220VAC 0.5A, 5VDC 0.5A
Installation Means	Wall mounted, Pipe type (Thread:M40*1.5)
Material of Body	Cast aluminum
Explosion-proof Index	Ex d IIC T6
Protection Grade	IP66
Electrical Interface	3/4"NPT(Female Screw)、1/2"NPT(Female Screw)
Transmit Distance	≤2000m (If more than 2000m, can add the repeater.)
Dimension	210 mm×140 mm×92 mm (L×W×H)
Weight	About 1.5Kg
Standards	GB15322.1-2003 , GB3836.1-2010 , GB3836.2-2010 , GB3836.4-2010
Warranty	12months
Certificate	CNEx, CE, RoHS

Target gas list:

Gas	Detecting Range	Alarm Threshold	Sensor Type
NH ₃	0-100 PPM	25 PPM / 50 PPM	Electrochemical sensor
Cl ₂	0-50.0 PPM	10 PPM / 20 PPM	
H ₂	0-1000 PPM	50 PPM / 100 PPM	

CH ₂ O	0-100 PPM	25 PPM / 50 PPM	
O ₂	0-30.0%vol	18.5%vol / 23.5%vol	
H ₂ S	0-100 PPM	10 PPM / 20 PPM	
HCl	0-30.0 PPM	5.0 PPM / 10.0 PPM	
HCN	0-50.0 PPM	5.0 PPM / 10.0 PPM	
PH ₃	0-20.0 PPM	0.3 PPM / 0.6 PPM	
HF	0-10.0 PPM	3.0 PPM / 6.0 PPM	
NO	0-250 PPM	25 PPM / 50 PPM	
CO	0-500 PPM	35 PPM / 70 PPM	
SO ₂	0-20.0 PPM	2.0 PPM / 10.0 PPM	
ClO ₂	0-50.0 PPM	0.3 PPM / 0.5 PPM	
NO ₂	0-20.0 PPM	1.0 PPM / 2.0 PPM	
C ₂ H ₄ O	0-100 PPM	10 PPM / 20 PPM	
O ₃	0-20.0 PPM	5.0 PPM / 10.0 PPM	
CH ₄	0-100%LEL	25%LEL / 50%LEL	Catalytic combustion sensor
C ₃ H ₈	0-100%LEL	25%LEL / 50%LEL	
H ₂	0-100%LEL	25%LEL / 50%LEL	
NH ₃	0-100%LEL	25%LEL / 50%LEL	
C ₂ H ₄ O	0-100%LEL	25%LEL / 50%LEL	
CH ₃ CH ₃	0-100%LEL	25%LEL / 50%LEL	
C ₂ H ₄	0-100%LEL	25%LEL / 50%LEL	
C ₄ H ₁₀	0-100%LEL	25%LEL / 50%LEL	
C ₄ H ₈	0-100%LEL	25%LEL / 50%LEL	
C ₇ H ₈	0-100%LEL	25%LEL / 50%LEL	
C ₈ H ₁₀	0-100%LEL	25%LEL / 50%LEL	
CH ₄ O	0-100%LEL	25%LEL / 50%LEL	
C ₂ H ₆ O	0-100%LEL	25%LEL / 50%LEL	
C ₃ H ₄ O	0-100%LEL	25%LEL / 50%LEL	
C ₂ H ₃ Cl	0-100%LEL	25%LEL / 50%LEL	
C ₃ H ₉ N	0-100%LEL	25%LEL / 50%LEL	
CH ₃ Br	0-100%LEL	25%LEL / 50%LEL	
CO ₂	0-5.0%vol	1.0%vol / 3.0%vol	NDIR infrared sensor
	0-5000ppm	800 PPM / 1500 PPM	
CH ₄	0-5.0%vol	1.0%vol / 3.0%vol	
	0-100%vol	5%vol / 10%vol	

Reach Us



SBS Offices Worldwide

GCC Offices

Fujairah Office

Office 10, Building C, Fujairah
Free Zone II, Fujairah, UAE

Tel: +971 9 224 6664
Mobile: +971 50 108 6086
Fax: +971 9 222 8888
P.O. Box : 50555 Fujairah

Dubai Office 1

Scientific Business Solutions LLC FZC
Business Gate Center, Unit 1005
Level 10, Ibn Batuta Gate Office, Jebel Ali 1
Dubai, UAE.

Tel: +971 4 550 7828
Mobile: +971 50 408 6086
Fax: +971 4 550 7801
P.O. Box : 334035 Dubai

Asia Offices

Ras Al Khaima Office

Al Hamra Village, Villa 570
Ras Al Khaimah, UAE

Tel: +971 7 226 9015
Mobile: +971 55 543 8506

Dubai Office 2

Scientific Business Solution Trading LLC
Business gate center, Unit 1005, level 10, Ibn
Batuta gate office, Jebel Ali 1, Dubai, UAE. Dubai.

Tel: +971 50408 6086
Fax: +971 45507801
P.O Box : 334035 Dubai

Africa Offices

Egypt Office 1

Office 4 Building 151
Spico, Suez , Egypt.

Tel: +20 62 365 3606
Mobile: +20 122 3719802
Fax: +20 62 365 3606
P.O. Box 284 Suez .

Egypt Office 2

Building 1155, area 201
Khaled Bin Alwaleed St Elsalam 1
Suez , Egypt.

Tel: +20 62 353 5435
Mobile: +20 122 3719802
Fax: +20 62 353 5435
P.O. Box: 284 Suez .

Europe Office

United Kingdom Office

Global Scientific Business Solutions LTD UK
Suite 15 London Networking Capital –
Chessington Business Center COX LANE Chessington,
Surrey—KT9 1SD

Tel: +44 20 3044 2458
Mobile: +44 75 7065 5514

USA Office

Plano, Texas Office

5830 Grantie Pkwy #100-248Plano, TX
75024

Tel: +1 (713) 557-0011
P.O. Box : 75024 TX

Labs & Service Centers

Thoban Lab

Thoban, Fujairah, UAE

Tel: +971 9 224 6664
Mob.: +971 50 108 6086

Habhab Lab

Habhab, RAK, UAE

Tel: +971 9 224 6664
Mob.: +971 50 108 6086

Taween Service Center

Taween, Fujairah, UAE

Tel: +971 9 224 6664
Mob.: +971 50 108 6086

your business partner شريك أعمالك

info@global-sbs.co.uk

+971 50 108 6086

<https://lnkd.in/d8YEzjP>

<https://lnkd.in/dqCDkSQ>

www.global-sbs.co.uk

info@sbs-website.com

<https://lnkd.in/dpUnmZ4>

<https://lnkd.in/dw3iY7e>

<https://lnkd.in/d3Dke6u>

www.sbs-website.com